

iD Click Ultimate 30

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	31 Moderate
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	5,50 mm
Wear layer thickness	EN ISO 24340	0,30 mm
Total weight	EN ISO 23997	8900 g/m ²
Binder content	EN ISO 10582	Type I
Surface treatment		TEKTANIUM ®
Embossing in Register		Yes
Bevelled edges		4 sides
Installation method		Click
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0197-0056-DoP-2022-11
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	≤ 0,15 %
Curl resultant to heat	EN ISO 23999	Average measured value : ≤ 0.10 %
Reaction to fire	EN 13501-1	≤ 1 mm
Residual indentation	EN ISO 24343-1	Bfl-s1
Impact sound reduction - ΔLw	EN ISO 717-2	Required value: ≤ 0,10 mm
Reduction of in-room impact noise	NF S31-074	Average measured value: 0,02 mm
Thermal resistance	EN ISO 10456	19 dB
Colour fastness to light	EN ISO 105-B02	Class C (≤ 85 dB)
Chemical resistance	EN ISO 26987	0,06 m ² •K/W
Slip resistance	DIN 51130	≥ 6
Slip resistance	EN 13893	Good resistance
Peeling Resistance	EN ISO 24345	R10
Underfloor heating		Class DS (μ ≥ 0,30)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		≥ 50N/50mm
Recycled content	ISO 14021	Suitable (subfloor temperature maximum 27°C)
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		Recyclable
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		20 %
Total VOC Emissions	EN 16516	10,60 kg CO ₂ eq /m ²
Dimensions and designs		9,01 kg CO ₂ eq /m ²
Plank	Plank 1200 x 200,5mm - 7 planks=1,684 m ² /box - 52 boxes/pallet	
Tile	Tile 640 x 320mm - 9 tiles=1,843 m ² /box - 48 boxes/pallet	
Number of designs available	22	



The above information is subject to modification for the benefit of further improvement (21/09/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.