

Technical Datasheet

PVC cove formers & cappings

Co-extruded PVC capping - CAP3

SKIRTINGS & COVING

DESCRIPTION

Co-extruded PVC capping in 2 parts used to finish the top of a resilient floor covering where it has been covered up the wall. Usually used with a cove former PA series.


Key features:

- Easy installation thanks to its two-parted construction.
- Perfect hygienic conditions guaranteed.
- Easy cleaning and maintenance.

Compatible flooring:

- Homogeneous & heterogeneous vinyls in rolls.

Main segments of application:



TECHNICAL INFORMATION

Product

Size (mm)	2700 length x 27 height
Unit weight (g)	127

Packaging

Pieces per box	25 (67.50lm)
Box size (cm)	3.14 x 0.18 x 0.06
Pallet size (m)	2.7 x 0.65 x 1.2
Boxes per pallet	40
Min. order	1 box

INSTALLATION

- Installation in 2 phases:
 - 1st part: glued to the wall
 - 2nd part: to be clipped
 - Use a contact adhesive: spread adhesive within the pre-marked sections of the subsurface with an appropriate brush.
- Spread adhesive on the backside of the capping.
- Stop at 1 cm from the angle of the wall.
 - When finishing skirting has to be fixed at 8 cm from the substrate; fix the « back » profile 1,5 cm below. No need to cut corners with the « back » profile.

CLEANING & MAINTENANCE

For regular cleaning, use standard neutral detergents (ph7) and a dedicated tool specific for capping cleaning.

ARTICLE CODE

		SAP Code	EAN Code
	Black RAL: 1500 NCS: S 9000 N	1445 000	3423128397666
	Wood colour matched RAL: 070 80 30 NCS: S 2020 Y 30 R	1445 002	3423128397680
	White RAL: 9003 NCS: S 0500 N	1445 001	3423128397673